

Notes

- DO NOT SCALE THIS DRAWING ON PRINT OR ELECTRONICALLY. WORK FROM FIGURED DIMENSIONS ONLY.
- No deviation from the details shown on this drawing is allowed without Campbell Reith Hill's prior permission in writing.
- Read this drawing with all Architects, Service Engineers and Campbell Reith Hill's relevant details and drawings.
- All work is to be in accordance with the relevant specifications issued by Campbell Reith Hill, British Standard Codes of Practice, Statutory requirements and the Contract Documents.
- DRAWING STATUS  
 S :- SCHEME ---- Outline/Scheme drawings for proposals, budgets etc.  
 D :- DESIGN DEVELOPMENT ---- Evolving final design drawings for approvals, tenders, billing etc.  
 C :- CONSTRUCTION ---- Fully developed drawings issued under instruction for construction.  
**ONLY STATUS C DRAWINGS TO BE USED FOR CONSTRUCTION.**

- PILE CAP & GROUND BEAM  
 SIDES - 50mm  
 BOTTOM COVER - 75mm  
 TOP COVER - 25mm  
 TOP COVER - 50mm (FOR PILE CAPS AT CAR PARK)

- COLUMN & WALLS  
 ALL SIDES - 25mm  
 ALL SIDES - 35mm (COLUMNS EXPOSED IN CAR PARK)

- SLABS  
 TOP COVER - 25mm  
 BOTTOM AND SIDES - 50mm

- MINIMUM LAP LENGTHS  
 B12 - 550mm  
 B16 - 750mm  
 B20 - 900mm  
 B25 - 1150mm  
 B32 - 1450mm

- ABBREVIATIONS  
 HOR : HORIZONTAL T1 : TOP FIRST LAYER  
 VERT : VERTICAL T2 : TOP SECOND LAYER  
 NF : NEAR FACE B1 : BOTTOM FIRST LAYER  
 FF : FAR FACE B2 : BOTTOM SECOND LAYER

REFERENCE DRAWING NO.:

RC DETAILS OF CORE BASE&COLUMN STARTER	- 8974-202
RC DETAILS OF COLUMN	- 8974-205
RC DETAILS OF GROUND BEAMS	- 8974-203
RC DETAILS OF GROUND FLOOR SLAB	- 8974-204

